

轴承型号 Bearing No.	外型尺寸 (mm) Boundary dimensions (mm)				相关安装尺寸 (mm) Mounting dimensions (mm)				重量 weight			轴承型号 Bearing No.
	d	D	B	r	da	da	Da	ra	参考 refer (kg)			
					min	max	max	max	ZR02	SI3N4	POM	
6302CE	17	42	13	1	20	22.5	37	1	0.0520	0.0350	0.0160	P6302
6803CE		26	5	0.3	19	19	24	0.3	0.0062	0.0036	0.0013	P6803
6903CE		30	7	0.3	19	19.5	28	0.3	0.0154	0.0090	0.0033	P6903
16003CE		35	8	0.3	19	20.5	33	0.3	0.0208	0.0121	0.0060	P16003
6003CE		35	10	0.3	19	21.5	33	0.3	0.0308	0.0180	0.0080	P6003
6203CE		40	12	0.6	21	23.5	36	0.6	0.0508	0.0296	0.0130	P6203
6303CE		47	14	1	22	25.5	42	1	0.0838	0.0489	0.0220	P6303
6403CE		62	17	1.1	23.5	27	55.5	1	0.2061	0.1203	0.0520	P6403
6804CE	20	32	7	0.3	22	22.5	30	0.3	0.0154	0.0090	0.0030	P6804
6904CE		37	9	0.3	22	24	35	0.3	0.0307	0.0180	0.0070	P6904
16004CE		42	8	0.3	22	24.5	40	0.3	0.0385	0.0200	0.0090	P16004
6004CE		42	12	0.6	24	25.5	38	0.6	0.0523	0.0305	0.0130	P6004
6204CE		47	14	1	25	26.5	42	1	0.0754	0.0450	0.0210	P6204
6304CE		52	15	1.1	26.5	28	45.5	1	0.1146	0.0669	0.0280	P6304
6404CE		72	19	1.1	26.5	28.5	65.5	1	0.31	0.1796	0.0800	P6404
6805CE		25	37	7	0.3	27	27	35	0.3	0.0160	0.0098	0.0000
6905CE	42		9	0.3	27	28.5	40	0.3	0.0385	0.0225	0.0100	P6905
16005CE	47		8	0.3	27	29.5	45	0.3	0.0450	0.0269	0.0110	P16005
6005CE	47		12	0.6	29	30	43	0.6	0.0610	0.0350	0.0150	P6005
6205CE	52		15	1	30	32	47	1	0.093	0.0540	0.0250	P6205
6305CE	62		17	1.1	31.5	36	55.5	1	0.1800	0.1037	0.0450	P6305
6405CE	80		21	1.5	33	37	72	1.5	0.4083	0.2400	0.1020	P6405
6806CE	30		42	7	0.3	32	32	50	1	0.0180	0.0100	0.0050
6906CE		47	9	0.3	32	34	57	1	0.0461	0.0269	0.0100	P6906
16006CE		55	9	0.3	32	42.5	65.5	1	0.0654	0.0383	0.0170	P16006
6006CE		55	13	1	35	36.5	53	1	0.0846	0.0490	0.0220	P6006
6206CE		62	16	1	35	38.5	60	1	0.15	0.0898	0.0380	P6206
6306CE		72	19	1.1	36.5	42.5	68.5	1	0.2700	0.1400	0.0660	P6306
6406CE		90	23	1.5	54	60	82	2	0.5475	0.3190	0.1400	P6406
6807CE		35	47	7	0.3	37	37	45	0.3	0.0231	0.0135	0.0050
6907CE	55		10	0.6	39	39	51	0.6	0.0661	0.0380	0.0140	P6907
16007CE	62		9	0.3	37	38	60	0.3	0.0769	0.0450	0.0210	P16007
6007CE	62		14	1	40	41.5	57	1	0.1138	0.0665	0.0290	P6007
6207CE	72		17	1.1	41.5	44.5	65.5	1	0.1753	0.1020	0.0550	P6207
6307CE	80		21	1.5	43	47	72	1.5	0.3422	0.2043	0.0890	P6307
6407CE	100		25	1.5	43	49	92	1.5	0.7090	0.4140	0.1800	P6407
6808CE	40		52	7	0.3	42	42	50	0.3	0.0262	0.0144	0.0060
6908CE		62	12	0.6	44	46	58	0.6	0.0900	0.0490	0.0220	P6908
16008CE		68	9	0.3	42	44	66	0.3	0.1000	0.0580	0.0250	P16008
6008CE		68	15	1	45	47.5	63	1	0.1423	0.0800	0.0370	P6008
6208CE		80	18	1.1	46.5	50.5	73.5	1	0.2800	0.1650	0.0700	P6208
6308CE		90	23	1.5	48	53	80	1.5	0.4900	0.2800	0.1200	P6308
6408CE		110	27	2	49	55	101	2	0.9460	0.5469	0.2400	P6408
6809CE		45	58	7	0.3	47	47.5	56	0.3	0.0290	0.0160	0.0070
6909CE	68		12	0.6	49	50	64	0.6	0.0970	0.0530	0.0240	P6909
16009CE	75		10	0.6	49	52	71	0.6	0.1300	0.0760	0.0320	P16009
6009CE	75		16	1	50	53.5	70	1	0.1769	0.1000	0.0460	P6009
6209CE	85		19	1.1	51.5	55.5	78.5	1	0.3200	0.1859	0.0810	P6209
6309CE	100		25	1.5	53	61.5	92	1.5	0.6400	0.3758	0.1600	P6309
6409CE	120		29	2	54	60	111	2	1.1800	0.6825	0.2900	P6409
6810CE	50		65	7	0.3	52	52.5	63	0.3	0.0438	0.0256	0.0100
6910CE		72	12	0.6	54	55	68	0.6	0.1000	0.0600	0.0260	P6910
16010CE		80	10	0.6	54	57	76	0.6	0.1300	0.0800	0.0340	P16010
6010CE		80	16	1	55	58.5	75	1	0.2000	0.1100	0.0500	P6010
6210CE		90	20	1.1	56.5	60	83.2	1	0.3500	0.2079	0.0880	P6210
6310CE		110	27	2	59	68	101	2	0.8382	0.4894	0.2000	P6310
6410CE		130	31	2.1	61	68	119	2	1.4300	0.8350	0.3600	P6410
6811CE		55	72	9	0.3	57	59	70	0.3	0.0615	0.0300	0.0160

轴承型号 Bearing No.	外型尺寸 (mm) Boundary dimensions (mm)				相关安装尺寸 (mm) Mounting dimensions (mm)				重量 weight			轴承型号 Bearing No.	
	d	D	B	r	da	da	Da	ra	参考 refer (kg)				
					min	max	max	max	ZR02	SI3N4	POM		
6911CE	60	80	13	1	60	61.5	75	1	0.1500	0.0800	0.0360	P6911	
16011CE		90	11	0.6	59	60	86	0.6	0.2000	0.1167	0.0490	P16011	
6011CE		90	18	1.1	61.5	64	83.5	1	0.2900	0.1700	0.0730	P6011	
6211CE		100	21	1.5	63	66.5	92	1.5	0.4800	0.2700	0.1200	P6211	
6311CE		120	29	2	64	72.5	111	2	1.0400	0.6080	0.2600	P6311	
6411CE		140	33	2.1	66	75	129	2	1.8456	1.0780	0.4400	P6411	
6812CE		65	78	10	0.3	62	64	76	0.3	0.0800	0.0400	0.0200	P6812
6912CE			85	13	1	65	66	80	1	0.1769	0.1033	0.0370	P6912
16012CE	95		11	0.6	64	65	91	0.6	0.2153	0.1257	0.0540	P16012	
6012CE	95		18	1.1	66.5	69	88.5	1	0.3007	0.1756	0.0790	P6012	
6212CE	110		22	1.5	68	74.5	102	1.5	0.6000	0.3502	0.1500	P6212	
6312CE	130		31	2	71	79	119	2	1.3200	0.7678	0.3300	P6312	
6412CE	150		35	2.1	71	80	139	2	2.1690	1.2660	0.5300	P6412	
6813CE	70		85	10	0.3	69	69	81	0.6	0.1000	0.0500	0.0250	P6813
6913CE		90	13	1	70	71.5	85	1	0.1700	0.0900	0.0400	P6913	
16013CE		100	11	0.6	69	70	96	0.6	0.2300	0.1340	0.0600	P16013	
6013CE		100	18	1.1	71.5	73	93.5	1	0.3153	0.1840	0.0800	P6013	
6213CE		120	23	1.5	73	80	112	1.5	0.7359	0.4290	0.1900	P6213	
6313CE		140	33	2.1	76	85.5	129	2	1.6200	0.9429	0.4100	P6313	
6814CE		75	90	10	2.1	74	74.5	86	0.6	0.1000	0.0512	0.0300	P6814
6914CE			100	16	0.6	75	77.5	95	1	0.2700	0.1500	0.0700	P6914
16014CE	110		13	1	74	76	106	0.6	0.3400	0.1900	0.0800	P16014	
6014CE	110		20	0.6	76.5	80.5	103.5	1	0.4422	0.2580	0.1200	P6014	
6214CE	125		24	1.1	78	84	117	1.5	0.8459	0.4939	0.2100	P6214	
6314CE	150		35	1.5	81	92	139	2	1.9610	1.1450	0.4900	P6314	
6815CE	80		95	10	2.1	79	79.5	91	0.6	0.1100	0.0600	0.0290	P6815
6915CE			105	16	0.6	80	82	100	1	0.3280	0.1886	0.0700	P6915
16015CE		115	13	1	79	81	111	0.6	0.3537	0.2096	0.0890	P16015	
6015CE		115	20	0.6	81.5	85.5	108.5	1	0.5000	0.2750	0.1200	P6015	
6215CE		130	25	1.1	83	90	122	1.5	0.9000	0.5300	0.2300	P6215	
6816CE		85	100	10	1.5	84	84.5	96	0.6	0.1200	0.0718	0.0300	P6816
6916CE			110	16	2.1	85	87.5	105	1	0.3380	0.1978	0.0750	P6916
16016CE			125	14	0.6	84	85	121	0.6	0.4600	0.2690	0.1200	P16016
6016CE	125		22	1	86.5	91	118.5	1	0.6400	0.3800	0.1700	P6016	
6216CE	140		26	0.6	89	95.5	131	2	1.1151	0.6511	0.2700	P6216	
6817CE	90		110	13	1.1	90	90.5	105	1	0.2000	0.1280	0.0510	P6817
6917CE			120	18	1.5	91.5	94.5	113.5	1	0.4768	0.2783	0.1100	P6917
16017CE			130	14	0.6	89	90	126	0.6	0.5000	0.2830	0.1300	P16017
6017CE		130	22	1	91.5	96	123.5	1	0.6600	0.3879	0.1800	P6017	
6217CE		150	28	0.6	94	102	141	2	1.3600	0.7900	0.3400	P6217	
6818CE		95	115	13	1.1	95	95.5	110	1	0.2100	0.1200	0.0500	P6818
6918CE			125	18	2	96.5	98.5	118.5	1	0.4999	0.2900	0.1100	P6918
16018CE			140	16	1	95	96	135	1	0.6537	0.3800	0.1700	P16018
6018CE	140		24	1.1	98	103	132	1.5	0.8382	0.5000	0.2300	P6018	
6218CE	160		32	0.6	100	102	145	2	1.6200	0.9429	0.4100	P6218	
6819CE	100		120	13	0.6	100	102	115	1	0.2300	0.1200	0.0570	P6819
6919CE			130	18	1.1	101.5	104	123.5	1	0.4600	0.2500	0.1200	P6919
16019CE			145	16	2	100	101	140	1	0.7000	0.3990	0.1700	P16019
6019CE		145	24	1	103								